



2024 Chevrolet Silverado 1500 Email for price

Dealer Information

To get more details or set up a test drive this vehicle

Call us now:(281) 719-3756 20403 I-45 North Spring, Texas 77388



- Stock #:P29353
- VIN:1HTKJPVM2RH047090
- Mileage:0
- Location:Spring, Texas 77388
- Body Style:Truck
- Int.Color:
- Ext.Color:Silver Ice Metallic
- Transmission:Automatic
- Engine:Duramax 6.6L Turbo-Diesel V8, B20-Diesel compatible 350 hp @ 2500 rpm, 750 lb.-ft. torque @ 1400 rp

Dealer Comments

Why look any further? Duramax 6.6L Turbo-Diesel V8, B20-Diesel compatible 350 hp @ 2500 rpm, 750 lb.-ft. torque @ 1400 rpm, 6-Speed A/T, Four Wheel Drive, and .

Installed Features

- Brake
- parking
- driveline park brake system|Daytime Running Lamps
- with automatic exterior lamp control|Horn
- single-note|Antenna
- fixed mast|Bumper
- front
- Black|Door handles
- Black|Front fender extension
- painted body color|Glass
- solar absorbing
- tinted|Grille guard screen
- insect protection (mounted behind grille)|Grille
- base

- molded in color
- Black|Headlamps
- halogen projector-beam|Lamps
- cargo area
- cab mounted with switch on center switch bank|Lamps
- rear
- stop/turn/backup (1-piece assembly) with license plate light|Lamps
- Smoked Amber roof marker|Spare tire delete|Wheel
- spare delete|A/C|Adjustable Steering Wheel|Assist handle
- front passenger and driver on A-pillars|Driver Information Center
- 4.2-inch diagonal color display
- includes driver personalization
- warning messages and vehicle information|Floor covering
- Graphite-colored rubberized-vinyl|Instrumentation
- 6-gauge cluster featuring speedometer
- fuel level
- engine temperature
- tachometer
- voltage and oil pressure|Interior trim
- Jet Black/Dark Ash (Required and only available with (H2S) Dark Ash seats with Jet Black interior accents.)|Power Driver Seat|Power Windows|Seat Belt
- Black|Speedometer
- miles/kilometers|Upfitter switch kit provides up to 4-30 amp circuits to facilitate installation of aftermarket electrical accessories located on the instrument panel|Visors
- driver and front passenger illuminated vanity mirrors|ABS|Alternator
- 150 amps|Axle lubricant
- front
- synthetic oil EmGard FE-75W-90|Axle lubricant
- rear
- synthetic oil EmGard FE-75W-90|Axle to End of Frame
- 49 (Requires wheelbase (ED5) 201
- (ED9) 165 or (ER2) 189. Not available with (G40)
- (GP1) or (GP8) rear air suspension.)|Axle
- Open rear axle
- non-locking rear|Batteries
- heavy-duty dual 1100 cold-cranking amps includes battery box mounted to left side under cab|Capped Fuel Fill|Emissions
- USA 50 State certified|Engine
- Duramax 6.6L Turbo-Diesel V8
- B20-Diesel compatible 350 hp @ 2500 rpm
- 750 lb.-ft. torque @ 1400 rpm|Exhaust brake|Exhaust system
- right side exit
- behind rear wheels (Requires (ED9) 165 wheelbase.)|Front axle
- 7
- 500 lb.
- Dana Spicer 60-256
- single-reduction
- front driving|Front suspension
- 7
- 500 lb. (3
- 402 kg) multi-leaf
- includes shock absorbers|Fuel tank
- rear only
- 40 gallon mounted between frame side rails and behind rear axle|Fuel
- diesel B20|GVWR
- 16
- 500 lb. (7484 kg) (Silverado 4500 HD 4WD models require one of the following combinations: (1) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension. (2) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (GR4) 13.5k rear suspension or (FU7) 15.5k rear suspension. (3) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (J27) 15.5k rear axle and one of the following rear suspensions: (91B) 13.5k LiquidSpring prep single volume rear suspension
- (91C) 13.5k LiquidSpring prep stacked volume rear suspension
- (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.)|Incomplete vehicle|Neutral-at-Stop Automatic transmission shifts to neutral when the service brake is depressed while the vehicle is at a complete stop
- and remains in neutral until the service brake is released|Power Steering|Rear axle

- 11
- 000 lb. (4
- 999 kg)|Rear axle
- 4.30 ratio Max road speed: 75 MPH|Rear suspension
- 11
- 000 lb. (4
- 990 kg) multi-leaf
- vari-rate|Trailer brake controller
- integrated|Trailer provisions
- trailering wire harness only
- trailer combined (Stop/Tail/Turn) connection socket and harness mounted at rear of frame.|Transmission shift control calibration
- fuel sense Performance|Wheelbase
- 165 (419.1 cm)
- 84 CA (Requires (F0C) 49 axle to end of frame
- (F0D) 63 axle to end of frame or (F0K) 91 axle to end of frame and (NPR) right side exit exhaust
- behind rear wheels. Requires (PCJ) Vocational Specific Heavy Suspension Package
- when ordering (FTA) 7
- 000 lb. Front axle/(FK6) 7
- 000 lb. Front suspension or (FTL) 8
- 000 lb. Front axle/(FSN) 8
- 000 lb. Front suspension and/or (FU7) 15
- 500 lb. rear suspension.)|6-speaker audio system|SILVER ICE METALLIC|

Sales Tax, License Fee, Registration Fee, Dealer Documentary Fee, Finance Charges, Emission Testing Fees and Compliance Fees are additional to the advertised price.